





ELECTRICAL SPECIFICATIONS		REVISIONS			
PASSBAND: TX=7.9 -8.4 GHz : RX=7.25-7.75 GHz INSERTION LOSS: .10 dB MAX VSWR: 1.2:1 MAX PORT-PORT ISOLATION: 40 dB MIN AXIAL RATIO: .75 dB MAX FINISH: CHEM FILMED PER MIL-C-5541, TYPE II PRESSUARIZATION: 5 PSIG		REV	DESCRIPTION	DATE	APPROVED
		-	INITIAL RELEASE	02-04-02	



-2 POLARIZER

UNLESS OTHERWISE SPECIFIED		SIGNATURES		DATE		 VertexRSI TM A TriPoint Global Company Antenna Products Division, Torrance, CA Facility 3111 Fujita Street, Torrance, CA 90505-4006	
DIMENSIONS ARE IN INCHES		DRAWN:	L. TOVALIN	02-10-93			
TOLERANCES-		CHECKED:	L. SPIELEDER	02-10-93		X-BAND POLARIZER (CAST ALUMINUM)	
SURFACE .XX ±.01		ENGRG:					
.XXX ±.002		ENGRG:					
.XXXX ±.0010		MFG:					
64 ✓ ANGLES ±0° 30'						SIZE: C FSCM NO. 50478 DRAWING NO. 110098	
MATERIAL:							
NEXT ASSY:							
		CADRA-DIRECTORY:				SCALE: 2/1	SHEET 1 of 3